

185-245 AC input
Cooling by free air convection
Ultra Slim size and 1U profile
LED indicator for power on
Withstand 5G vibration test
No load power consumption<0.3W
100% full load burn-in test
High efficiency, long life and high reliability



LVD CE RoHS COMPLIANT



İÇ MEKAN GÜÇ KAYNAKLARI 36W – 250W Sabit Voltaj XLS Serileri

XLS-36



XLS-60



XLS-100



XLS-150



XLS-200



XLS-250



MODEL	GÜÇ	VOLT	AMPER	ÖLÇÜ	KOLİ	LİSTE
XLS-36-12	36W	12VDC	3.00Amp	116*51*24mm	100	\$7,75
XLS-60-12	60W	12VDC	5.00Amp	139*51*24mm	100	\$9,60
XLS-100-12	100W	12VDC	8.50Amp	192*51*24mm	50	\$13,80
XLS-150-12	150W	12VDC	12.50Amp	192*51*24mm	50	\$15,70
XLS-200-12	200W	12VDC	16.50Amp	208*61*26mm	50	\$19,50
XLS-250-12	250W	12VDC	21.00Amp	226*61*26mm	50	\$21,65

MODEL	GÜÇ	VOLT	AMPER	ÖLÇÜ	KOLİ	LİSTE
XLS-36-24	36W	24VDC	1.50Amp	116*51*24mm	100	\$7,80
XLS-60-24	60W	24VDC	2.50Amp	139*51*24mm	100	\$9,60
XLS-100-24	100W	24VDC	4.10Amp	192*51*24mm	50	\$14,35
XLS-150-24	150W	24VDC	6.25Amp	192*51*24mm	50	\$16,25
XLS-200-24	200W	24VDC	8.25Amp	208*61*26mm	50	\$20,10
XLS-250-24	250W	24VDC	10.00Amp	226*61*26mm	50	\$23,00